

GSM106 BA PS

Universal phone-line simulator with integrated backup battery, data communication for board supervision via cloud.

MAIN FEATURES

- Backup battery management.
- Power supply and battery check, and related failure SMS.
- 220V Power supply.

SIZE

120x101x46 mm

TECHNICAL DATA

Input voltage: 220Vac to 12Vdc.

Maximum Electric current absorbed: 1 A.

UPS: battery charger 12 V.

Resting voltage: 24 V DC balanced.

Maximum current: 30 mA.

Ring voltage: 30 V eff. 25Hz +/- 5% balanced.

RS232 Data interface: maximum speed 115200 bps.

GSM radio module: Quad-band GSM 900/1800/1900 MHz.

GPRS radio module: class 10.

Installation: fixing on din bar.

COMBI GSM

Dedicated GSM gateway and data modem for Vega Auto-Dialers.

MAIN FEATURES

- Monitoring of VEGA Auto-Dialers via Cloud.
- Simplified wiring by only one connector.
- Power supply by Auto-Dialer.
- Caller ID visualization.
- SMS management.
- External antenna with magnetic base and 2.5 m. of wire.
- Remote control of GSM signal level.
- SIM credit control.
- PIN management.

SIZE

110x70x25 mm

TECHNICAL DATA

GSM radio module: quad-band 900/1800/1900 MHz.

GPRS radio module: class 10.

